


# STTT-V series thermocouple

STTT-V series thermocouple is welded by thermocouple wire with insulated cover. The product has one of the simplest structures with the fastest response time, and can be applied for fast temperature measurement in fields, such as healthcare, heating ventilation, refrigeration, environmental experiment, and etc.



	STTT-V	A	B	L	P	T	W	S
V Style Code	_____							
A Calibration	_____							
K=Type K E=Type E J=Type J T=Type T								
B Diameter of Conductor (mm)	_____							
1=0.1 2=0.2 3=0.32 6=0.6 ⚡Customized								
L Lead Wire Length (mm)	_____							
1=1000 2=2000 3=3000 ⚡Customized								
P Accuracy	_____							
I =Class I II=Class II								
T Temperature Range (°C)	_____							
5=-200~200 6=0~200 7=0~400 ⚡Customized								
W Lead Termination	_____							
0=None 1=M4 lugs ⚡Customized								
S Special Requirements	_____							
0=None ⚡Customized								

Note: 1. The 'Customized' option should be filled your requirements directly  
 2. Special Requirements' if there are any more options, please use the '/' fill it in seriate.

Order example: STTT-V-----AT-----B2-----L2-----P I -----T6-----W0-----S0  
style code Type T DiameterLeadwire lengthAccuracy I 0~200°C None None  
 0.2 2000mm